



24

CE DoP 705

Declaration of Performance

Regulation (EU) Nr. 305/2011

Decorative wall slimline

1	Harmonised technical standard	DIN EN 13986:2004+A1:2015
2	Usage	Coated wood-based material for interior use as a non-load-bearing component in dry areas
3	Manufacturer	akustikplus GmbH & Co. KG, Postfach 100353, D-83003 Rosenheim
4	Assessment and verification of constancy of performance	System 3 ^{*)}

Technical class	MDF according to EN 622-5
Panel thickness	16 - 19mm
Open area	≤ 34,5%

5	Essential characteristics	Declared performance
	Reaction to fire ^{*)}	EN 13501-1 Cs2 d0
	Emission fo formaldehyde ^{*)}	EN 717-1/-2 E1
	Pentachlorphenol content	EN 13986 - Kap. 5.18 ≤ 5 ppm
	Biological durability	EN 335 Class 1
	Transverse tensile strength	EN 319 > 1,0 N/mm ²
	Bending strength	EN 310 > 25 N/mm ²
	Water vapour permeability	EN 13986 - Tab. 9 NPD
	Airborne sound insulation	EN 13986 - Kap. 5.10 NPD
	Sound absorption	EN 13986 - Tab. 10 NPD
	Thermal conductivity	EN 13986 - Tab. 11 NPD

The performance of the product identified in (2) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

Michael Paringer,
Managing Director Technology

Stephanskirchen, 14.02.2024

^{*)} In accordance with the harmonised standard specified in (1), the inspection body/bodies NB 1322 IBS Linz, NB 0766 EPH Dresden has/have performed type testing according to the system specified in (4).