



Declaration of Performance

No. DOP_MMHG_101

1. Unique identifier code of the product type: product type 1 **glued laminated timber GL24c**
product type 2 **glued laminated timber GL24h**
product type 3 **glued laminated timber GL28c**
product type 4 **glued laminated timber GL28h**
product type 5 **glued laminated timber GL30c**
product type 6 **glued laminated timber GL30h**
2. Purpose: In buildings and bridges
3. Manufacturer: **Mayr-Melnhof Holz Gaishorn GmbH**
8783 Gaishorn am See 182, Austria
4. Authorised representative: **No external authorised representative**
5. System for assessment and verification of the constancy of performance:
System 1
- 6.a) Harmonised standard: **EN 14080:2013**
Notified body: **NB 1359 (Holzforschung Austria)**
7. Declared performance:

Essential characteristics	Performance
Mechanical properties covering the following: Modulus of elasticity, bending strength, compressive strength, tensile strength and shear strength as:	
Properties of timber and Strength of finger joints as	Strength class for: product type 1 GL24c product type 2 GL24h product type 3 GL28c product type 4 GL28h product type 5 GL30c product type 6 GL30h The allocation of the construction products supplied to the individual strength classes can be taken from the accompanying documents.
Geometrical data	For all product types: Widths of 80 mm to 280 mm Heights of 100 mm to 2,400 mm The relevant product dimensions can be taken from the accompanying documents.
Bonding strength as	
Strength of finger joints and	For all product types: See mechanical properties, strength of finger joints
Bonding strength of bonds between laminates	For all product types: Delamination test according to EN 14080, Annex C, Method B
Reaction to fire as	
Reaction to fire class	For all product types: D-s2, d0 pursuant to EN 14080, Table 11



Resistance to fire as	
Strength class and Geometrical data	characteristic density of the relevant strength class spruce (Picea Abies) see „Geometric data“
Emission of formaldehyde as	
Formaldehyde emission class	For all product types: E1
Release of other dangerous substances	
Release of other dangerous substances	For all product types: No performance declared (NPD)
Durability of bonding strength as	
Wood species, Adhesive	For all product types: spruce (Picea Abies) For all product types: Adhesive for finger joints: MUF, EN 301-I-90-FJ-0,3-S, PUR EN 15425 Adhesive for bonds between laminations: MUF, EN 301-I-90-GP-0,3-S
Durability of other characteristics (i.e. resistance against biological attack) as	
Laminations without preservative treatment	Durability against timber-destroying fungi according to EN 350 for all product types: DC 5

The performance of the above product fulfils the declared performance. The above-mentioned manufacturer has the sole responsibility for the preparation of the declaration of performance in accordance with the regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

Markus Thier
Operation Manager

.....
Gaishorn, 2023.05.10

Bernhard Waldner
General Manager

.....
Gaishorn, 2023.05.10



NB 1359

Mayr-Melnhof Holz Gaishorn GmbH
8783 Gaishorn am See 182 – Austria

DOP_MMHG_101

15

1359 – CPR - 0637

EN 14080:2013

Glued laminated timber made from conifer without preservative treatment to be used in buildings and bridges

Mechanical properties and resistance to fire as

– Strength class	product type 1: GL24c
– Geometrical data	Widths 80 mm - 280 mm Heights 100 mm - 2,400 mm

Bonding strength as strength of the

Finger joints	product type 1: GL24c
– Adhesive joints	Delamination test according to EN 14080, Annex C, Method B

Reaction to fire D-s2, d0

Emission of formaldehyde E1

Durability of bonding strength as

– Wood species	Spruce (<i>Picea abies</i>)
– Adhesive for face bonding between laminations	MUF, I GP 90S
– Adhesive for finger joints	MUF, I FJ 90S PUR EN 15425

Durability of additional characteristics

– Laminations without preservative treatment	Timber destroying fungi according to EN 350: DC 5
--	---



NB 1359

Mayr-Melnhof Holz Gaishorn GmbH

8783 Gaishorn am See 182 – Austria

DOP_MMHG_101

15

1359 – CPR - 0637

EN 14080:2013

Glued laminated timber made from conifer without preservative treatment to be used in buildings and bridges

Mechanical properties and resistance to fire as

– Strength class	product type 2: GL24h
– Geometrical data	Widths 80 mm - 280 mm Heights 100 mm - 2,400 mm

Bonding strength as strength of the

Finger joints	product type 2: GL24h
– Adhesive joints	Delamination test according to EN 14080, Annex C, Method B

Reaction to fire D-s2, d0

Emission of formaldehyde E1

Durability of bonding strength as

– Wood species	Spruce (<i>Picea abies</i>)
– Adhesive for face bonding between laminations	MUF, I GP 90S
– Adhesive for finger joints	MUF, I FJ 90S PUR EN 15425

Durability of additional characteristics

– Laminations without preservative treatment	Timber destroying fungi according to EN 350: DC 5
--	---



NB 1359

Mayr-Melnhof Holz Gaishorn GmbH

8783 Gaishorn am See 182 – Austria

DOP_MMHG_101

15

1359 – CPR - 0637

EN 14080:2013

Glued laminated timber made from conifer without preservative treatment to be used in buildings and bridges

Mechanical properties and resistance to fire as

– Strength class	product type 3: GL28c
– Geometrical data	Widths 80 mm - 280 mm Heights 100 mm - 2,400 mm

Bonding strength as strength of the

Finger joints	product type 3: GL28c
– Adhesive joints	Delamination test according to EN 14080, Annex C, Method B

Reaction to fire D-s2, d0

Emission of formaldehyde E1

Durability of bonding strength as

– Wood species	Spruce (<i>Picea abies</i>)
– Adhesive for face bonding between laminations	MUF, I GP 90S
– Adhesive for finger joints	MUF, I FJ 90S PUR EN 15425

Durability of additional characteristics

– Laminations without preservative treatment	Timber destroying fungi according to EN 350: DC 5
--	---



NB 1359

Mayr-Melnhof Holz Gaishorn GmbH

8783 Gaishorn am See 182 – Austria

DOP_MMHG_101

15

1359 – CPR - 0637

EN 14080:2013

Glued laminated timber made from conifer without preservative treatment to be used in buildings and bridges

Mechanical properties and resistance to fire as

– Strength class	product type 4: GL28h
– Geometrical data	Widths 80 mm - 280 mm Heights 100 mm - 2,400 mm

Bonding strength as strength of the

Finger joints	product type 4: GL28h
– Adhesive joints	Delamination test according to EN 14080, Annex C, Method B

Reaction to fire D-s2, d0

Emission of formaldehyde E1

Durability of bonding strength as

– Wood species	Spruce (<i>Picea abies</i>)
– Adhesive for face bonding between laminations	MUF, I GP 90S
– Adhesive for finger joints	MUF, I FJ 90S PUR EN 15425

Durability of additional characteristics

– Laminations without preservative treatment	Timber destroying fungi according to EN 350: DC 5
--	---



NB 1359

Mayr-Melnhof Holz Gaishorn GmbH

8783 Gaishorn am See 182 – Austria

DOP_MMHG_101

15

1359 – CPR - 0637

EN 14080:2013

Glued laminated timber made from conifer without preservative treatment to be used in buildings and bridges

Mechanical properties and resistance to fire as

– Strength class	product type 5: GL30c
– Geometrical data	Widths 80 mm - 280 mm Heights 100 mm - 2,400 mm

Bonding strength as strength of the

Finger joints	product type 5: GL30c
– Adhesive joints	Delamination test according to EN 14080, Annex C, Method B

Reaction to fire D-s2, d0

Emission of formaldehyde E1

Durability of bonding strength as

– Wood species	Spruce (<i>Picea abies</i>)
– Adhesive for face bonding between laminations	MUF, I GP 90S
– Adhesive for finger joints	MUF, I FJ 90S PUR EN 15425

Durability of additional characteristics

– Laminations without preservative treatment	Timber destroying fungi according to EN 350: DC 5
--	---



NB 1359

Mayr-Melnhof Holz Gaishorn GmbH
8783 Gaishorn am See 182 – Austria

DOP_MMHG_101
 15
 1359 – CPR - 0637

EN 14080:2013

Glued laminated timber made from conifer without preservative treatment to be used in buildings and bridges

Mechanical properties and resistance to fire as

– Strength class	product type 6: GL30h
– Geometrical data	Widths 80 mm - 280 mm Heights 100 mm - 2,400 mm

Bonding strength as strength of the

Finger joints	product type 6: GL30h
– Adhesive joints	Delamination test according to EN 14080, Annex C, Method B

Reaction to fire D-s2, d0

Emission of formaldehyde E1

Durability of bonding strength as

– Wood species	Spruce (<i>Picea abies</i>)
– Adhesive for face bonding between laminations	MUF, I GP 90S
– Adhesive for finger joints	MUF, I FJ 90S PUR EN 15425

Durability of additional characteristics

– Laminations without preservative treatment	Timber destroying fungi according to EN 350: DC 5
--	---